



KEY FEATURES

- Passive transceivers of 1 channel HDCV/HDTV/ AHD/ CVBS
- 2 unit blister
- 500 m passive to passive
- 650 m passive to active (CTD-494N)

FEATURES

- Passive transceiver, power is not required
- Live transmission of HDCV/HDTV/ AHD/ CVBS video signal
- Up to 500 m range passive to passive
- Up to 650 m range passive to active (CTD494N recommended)
- Compatible with adverse environments: without active electromagnetic interferences, high surge protection, ESD and lightningproof
- ABS case, coaxial cable connector incorporated
- 2 x blister unit served

SPECS

- 1 channel transceiver
- Transmission range (passive to passive):
- HDCV: 500 m at 720P, 150 m at 1080P
- HDTV: 240 m at 720P/1080P
- AHD: 500 m at 720P/960P, 420 m at 1080P
- CVBS: 600 m
- Video Coaxial Port: BNC male
- Twisted pair port: insertion terminal
- Video compatibility: CVI/TVI/AHD, PAL/NTSC/SECAM
- Bandwith: 0~75MHz
- Interference rejection: >60dB
- Coaxial port protection: 2KV Per: IEC610004-5
- Twisted pair protection: 2KV (differential mode), 4KV (common mode), Per: IEE610004-5
- ESD: Level 3, 1a contact discharge , Nivel 3, 1b air discharge
- Surge protection
- Storage temperature 20°C ~ +70°C
- Working temperature 10°C ~ +55C°
- RH 0% ~ 95% without condensation
- ABS plastic case
- Weight: 18 g