



KEY FEATURES

- RFID Mifare access control reader with keyboard
- Waterproof autonomous system, for outdoors
- Sensitive Sensitive touchscreen
- 30.000 users/cards
- 150.000 events
- Card authentication, password, card+password
- Interfaz at PC TCP/IP or RS485
- Wiegand reader interface or RS485
- door sensor input and exit button
- Lock exit

FEATURES

- RFID Mifare access control reader with reader
- Waterproof standalone system, for outdoors
- 32 bit processor
- 16MB memory
- Card type: Mifare (13,56MHz)
- Card reading range: 3~6 cm
- Response time of card reader <0,1s
- User/cards capacity: 30.000
- Event/reg capacity: 150.000
- Autentification: Card / Password / card+password
- Sensitive touchscreen with blue backlight
- Input interface: 1 door sensor, 1 exit button
- Output interface: 1 relay for lock
- Bip tone buzzer
- Voice message: not available
- PC connection via TCP/IP or RS485
- Connection to reader via Wiegand or RS485
- Alarm by door aperture, intrusion, lock or manipulation
- Anti-passback, multi-card aperture
- Software assistance
- Soporta 128 horarios diferentes y periodos de vacaciones
- La función watch-dog garantiza que el dispositivo no se detenga
- Power supply: 9V ~ 15V DC, 200 mA
- Working temperature: -30°C ~ +60°C
- IP67
- RH: ≤95%
- Dimensions: 62 x 23 x 142 mm
- Weight: 500 g
- Surface installation