

EPOE MANAGED SWITCH (L2) OF 24X POE/POE+/HI-POE + 2X 10/100/1000 BASE-T + 2 X COMBO 1000 BASE-X



KEY FEATURES

- ePoE managed switch (L2) of 24x PoE/PoE+/Hi-PoE + 2x 10/100/1000 Base-T + 2 x Combo 1000 Base-X
- ePoE technology and PoC
- Up to 800 m ePoE 10Mbps
- Lightning-proof 4KV
- Power supply included

FEATURES

- ePoE managed switch (L2)
- PoE transmission > 800 m over Ethernet at 10Mbps, or 300 m at 100Mbps thanks to ePoE technology
- Compatible with PoE and PoC technology
- Surveillance system design more flexible, improves reliability and saves costs in wiring and construction
- 24x 10/100 Base-T (PoE)
- 2x 10/100/1000 Base-T
- 2x 1000 Base-X (Combo)
- PoE consumption: 60W (Hi-PoE, ports 1 and 2), ≤30W (each port), ≤360W total
- PoE protocols: IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE
- Switching capacity 8,8Gbps
- Package transference rate 6,55Mpps
- Package memory buffer: 2,75MB
- MAC address: 4K
- Flux control: half-duplex and full-duplex supported
- Power supply: 100V~240V AC, 50/60Hz
- Working temperature: -10°C ~ +55°C
- RH 10~90%
- Lightning-proof: 4KV (common mode), 2KV (differential mode)
- Dimensions: 440 x 300 x 44 mm
- Weight: 3,12 kg