

4 CHANNELS IP NVR (EXPANDABLE TO 8 CHANNELS VIA SWITCH DAHUA-1578)



KEY FEATURES

- 4 channels IP NVR (expandable to 8 channels via switch DAHUA-1578)
- H.265/H.264
- GPS, 3G/4G and WiFi module included
- Playback up to 4 channels
- Recording: 4K/8MP, 5MP, 3MP, 1080P, 720P, up to 200 Mbps

RELATED PRODUCTS



FEATURES

- 4 channel mobile NVR, H.265/H.264
- 4 IP inputs
- You can add 4 extra IP cameras via mobile switch DAHUA-1578 (MJHJ4P)
- LINUX O/S
- H.265/H.264
- VGA output
- Aviation connector
- 2 way audio: 1 MIC in / 1 MIC out
- 4K live display
- Output division: 1, 4
- Display resolution: 1080P (1920x1080), SXGA (1280x1024), 720P (1280x720), XGA (1024x768)
- Privacy mask: 4 rectangular zones (for each camera)
- Recording resolution: 4K/8MP (3890x2160), 5MP, 3MP, 1080P (1920x1080), 720P (1280x720), D1 (704x576), HD1 (352x576), 2CIF (704x288), CIF (352x288), QCIF (176x144)
- Recording speed: 200 Mbps
- Bitrate: 48 ~ 8.192 Kbps
- Simultaneous playback up to 4 channels
- OSD
- Motion detection adjustable of 396 zones (22x18 grid)
- Power supply: 1x SATA (up to 2TB per disc, not included)
- SD card slot up to 128GB (card is not included)
- Alarm: 6 in / 2 out (1 control +12V)
- 3G/4G and WiFi communication module incorporated
- High precision GPS module incorporated
- Network interface: RJ45 (10/100M)
- 4x PoE+ (IEEE802.3 af/at) M12 aviation connector
- Network protocols: TCP/IP, UDP, DHCP, DNS, Filter IP, PPPOE, DDNS, FTP, Email, Servidor alarma
- ONVIF Versión 2.3
- Remote access up to 128 users
- Compatible with iOS and Android
- 2x USB 2.0
- 1x RS232 for communication with PC and keyboard
- 1x RS485 for PTZ control
- Bus CAN supported
- Gyroscope
- Power supply: 6V ~ 36V CC
- Consumption: <13W (without discs)
- Working temperature: -30°C ~ +60°C
- RH: 10%~95%
- Dimensions: 180 x 210 x 50 mm
- Weight: 3 kg (without HDD)