

2 PASSIVE VIDEO TRANSCeptORS HDCVI/HDTVl/AHD/CVBS OF 1 CHANNEL OF LIVE TRANSMISSION UP TO 4K (CVI)



## KEY FEATURES

- 2 passive video transceptors HDCVI/HDTVl/AHD/CVBS of 1 channel of live transmission up to 4K (CVI)
- Power supply is not required
- Up to 200 meters @4K/6MP/5MP/4MP

## SPECS

- Pack of 2 transceptors HDCVI/HDTVl/AHD/CVBS
- Live transmission of 1 HDCVI channel (compatible with TVI/AHD/CVBS)
- Passive, power supply is not required
- Excellent capacities against overvoltage, antistatic and anti-interference
- BNC female connector and screw terminal connections
- HDCVI transmission range: up to 400m @720P, up to 250m @1080P, up to 200m @4MP/6MP/4K
- HDTVl transmission range: up to 400m @720P, up to 250m @1080P, up to 200m @4MP/5MP
- AHD transmission range: up to 400m @720P, up to 250m @1080P, up to 200m @4MP/5MP
- Supported resolution: 4K (CVI), 6MP (CVI), 5MP, 4MP, 1080P, 720P
- Cable UTP Cat5e/6
- BNC male impedance: 75 ohms
- UTP impedance cable: 100 ohms
- Temperatura de almacenamiento de -40°C ~ +80°C
- Temperatura de funcionamiento de -30°C ~ +70°C
- RH: <95Hz
- ABS plastic case (black color)
- Dimensions: 173,8 x 19,5 x 21 mm
- Weight: 40 g