

CCTV 6 IN 1 MULTIFUNCTION TESTER, 7" TOUCHSCREEN

KEY FEATURES

- CCTV 6 in 1 multifunction tester, 7" touchscreen
- CVI up to 4MP, TVI/AHD up to 5MP, SDI and IP H.265/H.264 of 4K
- Built in WiFi.Audio in/out
- PTZ control
- UTP test
- PoE output
- 12V and 5V power supply output
- Onvif supported
- HDMI in/out 1080P
- 12V DC



ONVIF HDCVI™ HDTVI AHD
CVBS



FEATURES

- 6 in 1 CCTV multifunction tester (CVBS, CVI, TVI, AHD, SDI, IP)
 - 7" touchscreen (1200x800 pixels)
 - 4K and H.265/H.264 decoding supported with stream 1 with display
 - HDMI input signal, 1080P supported
 - HDMI output with 1920x1080 resolution
 - IP/analog dual test (analog camera test and simultaneous IP)
 - Drop-down menu, shortcut button
 - Built in WiFi: It allows to receive images of WiFi cameras and supports the creation of WiFi hotspot
 - HD-TVI 3.0 and HD-CVI 3.0 supported with CVI image camera test of 4MP and TVI of 5MP
 - AHD/CVI/TVI camera test supports: snapshots, recording and video playback and 4x zoom
 - CVBS loop test: Transmits or receives analog video signal
 - IP Onvif camera test, 4K resolution supported
 - Display of analog camera images: PAL and NTSC auto adapt
 - Fast Onvif: with a key we generate a test report, including the IP address, resolution and decoding
 - IP camera connection via RJ45 and WiFi, 1080p supported
 - Tester can rotate 180°, ideal for cable connection and power supply
 - Live display
 - PTZ control, snapshot, video recording, playback
 - TV output with bar color generator
 - UTP cable test: TDR function (to locate and place broken UTP cable broken points), connection status, cable sequence display, test report saving
 - PoE voltaje measurement, PING test, IP address scanning, port intermittence, etc.
 - **Digital multimeter:**
 - AC/DC voltage
 - AC/DC intensity
 - Resistance / Diodes / Continuity
 - Capacitance (capacitors)
 - **Fiber optic meter:**
 - Power meter
 - Visual fault locator
 - 48V DC PoE output: Provides temporary power to PoE cameras
 - Power supply output: 12V /2A and 5V /2A
 - Audio in /out
 - LED lantern, calculators, players and other tools / applications
 - Power supply: 12V DC /2A
 - Incorporates 7.4V lithium polymer battery, 5400mAh
 - Working temperature: -10°C ~ +50°C
 - Dimensions: 240 x 145 x 46 mm
 - Weight: 620 g
- Apps included: EVOPLUS, HYUVMS, ASMS, HYU CONNECT, HYUPLUS