



KEY FEATURES

- Mifare 13,56 MHz card reader, IK10 vandal protection
- 50 mm reading range
- Keyboard incorporated
- Wiegand 26/34 communication
- RS485
- Suitable for outdoors

FEATURES

- Mifare reader
- 32 bit processor
- Reader status display via LED indicator
- DIP micro switch
- Can read ID card number
- Watchdog design for repairing itself in case that exception occurs, to ensure the long service life of the reader
- Wiegand 26/34 protocol and RS485 interface
- Zumbador incorporado para identificar el estado de lectura
- Tamperproof alarm
- Online upgrade function (under the 485 communication mode), and card reader can degrade to preupgrade status in case of upgrading failed
- Resistant to high and low temperatures
- Polycarbonate and zincalloy material shell
- IK10
- IP65

SPECS

- 32 bit processor
- Card reader: Mifare 13,56MHz
- Reader range: ≤50 mm
- ID configuration: DIP micro switch
- 12 key keyboard
- Acoustic signal incorporated
- Wiegand 26/34 communication
- LED indicators for power and status
- IP65
- IK10
- Power supply: 12V DC, 500 mA
- Consumption: ≤2W
- Working temperature: 20°C ~ +65°C
- Working RH: 10% ~ 90%, without condensation
- Dimensions: 118 x 76 x 23 mm
- Weight: ≤520 g