

5 IN 1 MULTIFUNCTION CCTV TESTER WITH 4" TFT DISPLAY WITH TVI/CVI/AHD (3.0) SUPPORT UP TO 3MP/4MP AND IP H.265 OF 4K



ONVIF HDCVI HDTVI AHD
CVBS

KEY FEATURES

- 5 in 1 multifunction CCTV tester with 4" TFT display with TVI/CVI/AHD (3.0) support up to 3MP/4MP and IP H.265 of 4K
- Audio input/output
- PTZ control
- UTP test
- TDR function
- PoE output
- 12V power supply output
- Onvif supported
- BNC input/output

- 5 in 1 CCTV multifunction tester (CVBS, CVI, TVI, AHD, IP)
- 4" TFT display (800x480 pixels), 16,7 million color, adjustable brightness
- H.265 and 4K @ 30 fps
- Onvif, RTSP and RTP protocol supported
- IP configuration: static IP, DHCP client, DHCP server
- IP camera test: Camera discovery, real-time video, camera configuration, PTZ control, Onvif device discovery through IP segments
- 10/100/1000M Ethernet link test, loop detect, DHCP client and server Ethernet traffic flow monitor, link quality test
- 2x RJ45 Gigabit Ethernet ports
- PD input test and voltage detection from power supply
- PAL/NTSC, HDCVI/HDTVI/AHD (3.0) with automatic recognition
- 1 BNC input / 1 BNC output
- 8X digital zoom, screenshot, H.264 video recording (HD coaxial video not supported)
- Generate PAL / NTSC video signal of various test pattern
- Generate HD-CVI, HD-TVI, AHD video signal of various test pattern (720P/1080P)
- 1 audio input for audio test
- RS485 port and coaxial interface input for PTZ control
- Coaxial PTZ control, Pelco-D/P, Samsung, Panasonic, Lilin, Yaan, etc.
- Baud speed: 150/300/600/1200/2400/4800/9600/19200bps
- TDR test of RJ45 cable: Test the length of four wire pairs. Maximum 200 meters, the resolution of 1 meter
- 2 pcs 35lm LED light, astigmatism
- 48V DC /15W PoE output: temporal power supply to PoE cameras
- 100V ~ 230V AC input, 50/60Hz
- Power supply output: 12V /2A
- 7.4V lithium-ion polymer battery, capacity 22.2Wh, about 10 hours working time.
- POE charging, power 10Wmax. Charging time 3~4 hours
- Power key, 12 control keys, QWERTY flip keyboard with 43 keys
- Auto Power Off (5 to 60 minutes configuration)
- Working temperature: -10°C ~ +55°C
- RH30%~90%
- Dimensions: 190 x 113 x 37mm
- Weight: 620 g