

4 IN 1 DOME PRO SERIES WITH IR OF 40 M FOR OUTDOORS



**HDCVI™ HDTVI AHD CVBS**  
**EMP**

**KEY FEATURES**

- 4 in 1 dome PRO series with IR of 40 m for outdoors
- 1/2,8" CMOS at 1080P
- 4 in 1 output (HDCVI / HDTVI / AHD / 960H) from switch OSD
- ICR filter
- 2,8 ~ 13,5 mm varifocal lens
- OSD, AWB, AGC, 2D/3D-DNR, WDR true, Defog, motion detection and privacy mask
- IP66
- 3AXIS
- 12V DC

**FEATURES**

- 1/2,8" Sony® STARVIS™ CMOS sensor, 2,16 MP
- Digital WDR
- Automatic Defog, HLC, privacy mask, motion detection, 32X Sense Up
- 2D/3DDNR, anti-flare effect
- 4 in 1 video output selectable by OSD switch

**SPECS**

- 1/2,8" Sony® STARVIS™ CMOS sensor, 2,16 MP
- Digital resolution: 1080P (1920x1080) @25 fps
- Analog resolution 700 horizontal lines
- 4 in 1 output (from OSD switch): HDCVI / HDTVI / AHD / 960H
- Removable mechanical filter
- 0,1 lux (color) / 0 lux IR On
- Smart IR: 3 led array, 40 meters
- 2,8 ~ 13,5 mm varifocal lens
- OSD via coaxial (only on CVI, TVI, AHD; 300 meter range)
- Automatic White balance
- Automatic Gain Control
- 2D/3DDNR
- Digital WDR
- Motion detection: 4 zones
- Privacy mask: 16 zones
- Defog
- Storage temperature: 20°C ~ +60°C
- Working temperature: 10°C ~ +60°C
- RH: <90% (without condensation)
- IP66
- Power supply: 12V DC (±10%)
- Consumption: <6W
- 3AXIS: wall and ceiling installation
- Dimensions: 119 (W) x 90 (H) x 130 (L) mm
- Weight: 510 g