

4 IN 1 DOME PRO SERIES WITH IR OF 40 M FOR OUTDOORS



HDCVI™ HDTVI AHD CVBS
BMP

KEY FEATURES

- 4 in 1 dome PRO series with IR of 40 m for outdoors
- 1/2,5" CMOS, 8MP
- 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switch from OSD
- ICR filter
- 2,8 ~ 12 mm motor lens with autofocus
- OSD, AWB, AGC, 2D/3D-DNR, WDR true, Defog, motion detection and privacy mask
- IP66
- 3AXIS
- 12V DC

FEATURES

- 1/2,5" Sony® STARVIS™ CMOS sensor, 8 MP
- WDR true
- Auto Defog, HLC, privacy mask, motion detection, 32X Sense Up
- 2D/3DDNR, anti-flare effect
- 4 in 1 video output selectable by OSD switch

SPECS

- 1/2,5" Sony® STARVIS™ CMOS sensor, 8,51 MP
- Digital resolution: 4K/8MP (3840x2160) @15 fps
- Analog resolution: 700 horizontal lines
- 4 in 1 output (from OSD switch): HDCVI / HDTVI / AHD / 960H
- Removable mechanical filter
- 0 lux IR On
- Smart IR: 3 leds array, 40 meters
- 2,8 ~ 12 mm motor lens with autofocus
- OSD via coaxial (only on CVI, TVI, AHD; 300 meters range)
- Automatic White Balance
- Automatic Gain Control
- 2D/3DDNR
- WDR true
- Motion detection: 4 zones
- Privacy mask: 16 zones
- Defog
- Storage temperature: 20°C ~ +60°C
- Working temperature: 10°C ~ +60°C
- RH: <90% (without condensation)
- IP66
- Power supply: 12V DC (±10%)
- Consumption: <6,5W
- 3AXIS: wall and ceiling installation
- Dimensions: 119 (W) x 90 (H) x 130 (L) mm
- Weight: 510 g