

UV-39 / IPC3232ER-DV

Antivandal varifocal dome with IR up to 30 meters, 2MP



FEATURES

- 1/3" CMOS low light
- 2 MP: 1920 x 1080 @25 fps (triple stream)
- Removable mechanical filter
- Smart IR up to 30 meters
- 2.8~12 mm varifocal lens
- WDR real, ROI, corridor mode
- Privacy mask 4 zones
- Micro SD up to 128GB (not included)
- IP66, IK10
- 2AXIS
- PoE supported

CAMERA	
Image sensor	1/3" Progressive Scan CMOS, 2 MP
Lens	2.8~12 mm, F1.4, 100°
Shutter	Auto / Manual / 1/6~1/8000 s
Day/night	ICR automatic commutation
Minimum illumination	0,03 lux F1.4 color / 0,01 lux F1.4 B/W
Smart IR	30 m
Signal to noise ratio	>52dB
Video output	1 BNC
WDR	Optical (up to 120dB)
VIDEO	
Resolution	1920 x 1080
Video compression	H.264, MJPEG
Frames per second	25 fps (1080P, 720P, D1)
ROI	Supported
Corridor mode	9:16
Stream	Triple
OSD	Up to 8 languages
Privacy mask	4 zones
AUDIO	
Audio	Bidirectional
Audio compression	G.711
NETWORK	
Network ports	1 RJ45 10M/100M Base-TX Ethernet
Network protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, Qos, NTP, FTP, HTTP, SNMP, SIP
Integration	ONVIF, IMOS, API
Alarm	1 input / 1 output
GENERAL	
Storage	Micro SD up to 128GB (not included)
Power supply	12V CC, PoE (IEEE802.3 af)
Consumption	6.6 W max. (PoE :max.7.2 W)
Working temperature	-40°C ~ +60°C, HR <90% (without condensation)
Protection	IP66, IK10
Dimensions	Ø148 x 111.3 mm
Weight	750 g

ACCESORIES



UV-48
Wall mount

DIMENSIONS

