




















Choose HYUNDAI!











The brand that's causing sensation in the european market

ANALOG CAMERAS		
Reference	Picture	Description
HYU-510		4 in 1 bullet camera LITE series with Smart IR of 20 m for outdoors. 1MP CMOS. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). 2,8 mm (92°) fixed lens. ICR. IP66. 3AXIS. 12V DC.
HYU-502		4 in 1 dome PRO series with Smart IR of 20 m for outdoors. 2MP CMOS. 4 in 1 (HDCVI / HDTVI / AHD / 960H). 2,8 mm fixed lens (103°). ICR. OSD, digital WDR. IP66. 3AXIS. 12V DC.
HYU-503		4 in 1 dome PRO series with Smart IR of 20 m for outdoors. 2MP CMOS. 4 in 1 (HDCVI / HDTVI / AHD / 960H). 2,8 mm fixed lens (103°). ICR filter. OSD, digital WDR. IP66. 3AXIS. 12V DC.
HYU-504		4 in 1 dome PRO series with Smart IR of 20 m, for outdoors. CMOS, 2MP. 4 in 1 (HDCVI / HDTVI / AHD / 960H). 2,8 mm fixed lens (103°). ICR filter. OSD, digital WDR. IP66. 3AXIS. 12V DC.
HYU-511		4 in 1 bullet camera PRO series with Smart IR of 20 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). 2,8 mm fixed lens (103°). ICR filter. OSD, ATW/MWB, AGC, BLC, digital WDR. IP66. 3AXIS. 12V DC.
HYU-505		4 in 1 dome PRO series with Smart IR of 40 m for outdoors. CMOS, 2MP. 4 in 1 (HDCVI / HDTVI / AHD / 960H). 2,8 mm fixed lens (103°). ICR filter. OSD, digital WDR . IP66. 3AXIS. 12V DC.
HYU-514		TVI bullet camera PRO series with Smart IR of 20 m for outdoors. 3MP CMOS. HD-TVI video output. 2,8 mm fixed lens (84°). ICR filter. OSD, ATW/MWB, AGC, BLC, digital WDR, DNR. IP66. 3AXIS bracket. 12V DC.
HYU-387		HD-TVI bullet camera PRO series with Smart IR of 20 meters, for outdoors. 2MP CMOS. HD-TVI video output. 2,8 mm fixed lens (103°). ICR filter. ATW, AGC, DNR. IP66. 3AXIS bracket. 12V DC. PoC compatible.
HYU-513		4 in 1 bullet camera PRO series with Smart IR of 20 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). 2,8 mm fixed lens (103°). ICR filter. OSD, digital WDR. IP66. 3AXIS. 12V DC.











ANALOG CAMERAS

Reference	Picture	Description
HYU-506		4 in 1 dome PRO series with Smart IR of 20 m for outdoors. CMOS, 2MP. 4 in 1 (HDCVI / HDTV / AHD / 960H). 2,8 mm fixed lens (103°). ICR filter. OSD, digital WDR. IP66. 3AXIS. 12V DC.
HYU-507		HDTV dome PRO series with Smart IR of 40 m for outdoors. 3MP CMOS. HD-TVI video output. 2,8 mm (84°) fixed lens. ICR filter. OSD, ATW/MWB, AGC, BLC, digital WDR. IP66. 3AXIS. 12V DC.
HYU-566		HD-TVI dome PIR series with Smart IR of 20 m and motion detection by active PIR, for outdoors. 2MP CMOS. HD-TVI video output. 2,8 mm lens (103°). 0,01 lux color. ICR. OSD, ATW, AGC, BLC, DNR, mirror and image adjustment. Visual alarm via white led. IP67. 3AXIS. 12V DC.
HYU-512		4 in 1 fixed dome PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 ~ 12 mm varifocal lens (102,25°~32°). ICR. OSD, ATW/MWB, AGC, BLC, Digital WDR. IP66. 3AXIS. 12V DC.
HYU-389		HD-TVI fixed dome PRO series with Smart IR of 20 m for outdoors. 2MP CMOS. HD-TVI video output. 2,8 mm fixed lens (103°). ICR filter. ATW, AGC, DNR. IP66. 3AXIS. 12V DC. PoC compatible.
HYU-487		4 in 1 dome PRO series with Smart IR of 20 m for indoors. 5MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 mm fixed lens (85,5°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, brightness, sharpness, mirror. 3AXIS. 12V DC.
HYU-515		4 in 1 dome PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 ~ 12 mm varifocal lens (102,25°~32°). ICR filter. OSD, ATW/MWB, AGC, BLC, digital WDR. IP66. 3AXIS. 12V DC.
HYU-516		4 in 1 dome PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 ~ 12 mm varifocal lens (102,25°~32°). ICR filter. OSD, ATW/MWB, AGC, BLC, digital WDR. IP66. 3AXIS. 12V DC.
HYU-518		4 in 1 dome PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 ~ 12 mm varifocal lens (114,5°~35,1°). ICR filter. OSD, ATW, AGC, BLC, digital WDR, DNR, mirror mode, Anti-flicker, motion detection and privacy mask. IP66. 3AXIS. 12V DC.
HYU-485		4 in 1 bullet camera PRO series with Smart IR of 20 m for outdoors. 5MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 mm fixed lens (85,5°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, brightness, sharpness, mirror. IP67. 3AXIS bracket. 12V DC.





ANALOG CAMERAS

Reference	Picture	Description
HYU-488		4 in 1 dome PRO series with Smart IR of 20 m for outdoors. 5MP CMOS. 4 in 1 (HDCVI / HDTVI / AHD / 960H). 2,8 mm (85,5°) fixed lens. ICR. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, brightness, sharpness, mirror. IP67. 3AXIS. 12V DC.
HYU-568		HD-TVI dome PIR series with Smart IR of 20 m and motion detection by active PIR, for outdoors. 5MP CMOS. HD-TVI video output. 2,8 mm lens (85,5°). 0,01 lux color. ICR. OSD, ATW, AGC, BLC, DNR, mirror and image adjustment. Visual alarm via white led. IP67. 3AXIS. 12V DC.
HYU-486		4 in 1 vandal dome PRO series with Smart IR of 20 m, for outdoors. CMOS, 5MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). 2,8 mm (85,5°) fixed lens. ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, brightness, sharpness, mirror. IP67, IK10. 3AXIS. 12V DC.
HYU-517		4 in 1 bullet camera PRO series with Smart IR of 40 m, for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HD-TVI / AHD / 960H). 2,8 ~ 12 mm varifocal lens (102,25°~32°). ICR filter. OSD, ATW/MWB, AGC, BLC, digital WDR. IP66. 3AXIS bracket. 12V DC
HYU-570		HD-TVI dome PRO series with Smart IR of 20 m for outdoors. 5MP CMOS. HD-TVI video output. 2,8 mm lens (85,5°). ICR. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, image adjustment. IP67. 3AXIS. 12V DC. Compatible with PoC.af.
HYU-481		HD-TVI bullet camera PIR series with Smart IR of 20 m and motion detection by active PIR, for outdoors. 2MP CMOS. HD-TVI video output. 2,8 mm fixed lens (103,5°). 0,005 lux. ICR filter. OSD, ATW, MWB, AGC, BLC, real WDR 120dB, 3D-DNR, mirror, motion detection and privacy mask. Visual alarm by white led. IP67. 3AXIS bracket. 12V DC.
HYU-482		HD-TVI fixed dome PIR series with Smart IR of 20 m and motion detection by active PIR, for outdoors. 2MP CMOS. HD-TVI video output. 2,8 mm fixed lens (103,5°). 0,005 lux. ICR filter. OSD, ATW, MWB, AGC, BLC, real WDR 120dB, 3D-DNR, mirror, motion detection and privacy mask. Visual alarm by white led. IP67. 3AXIS. 12V DC.
HYU-509		HDTVI dome StarLight with Smart IR of 40 m for outdoors. 2MP CMOS. HDTVI video output. 2,8 ~ 12 mm (103°~32,1°) motor lens with autofocus. ICR filter. OSD, ATW/MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, mirror mode, sharpness and brightness adjustment, motion detection and privacy mask. IP67. 3AXIS. 12V DC.
HYU-390		HD-TVI fixed dome PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. HD-TVI video output. 2,7 ~ 12 mm varifocal lens (102,25°~32°). ICR. ATW, AGC, DNR. IP66. 3AXIS. 12V DC. PoC compatible .
HYU-388		HD-TVI bullet camera PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. HD-TVI video output. 2,7 ~ 12 mm varifocal lens (102,5°~32°). ICR filter. ATW, AGC, DNR. IP66. 3AXIS bracket. 12V DC. PoC compatible.





ANALOG CAMERAS










Reference	Picture	Description
HYU-547		HD-TVI StarLight with Smart IR of 20 m, for indoors. 2MP CMOS. HDTV video output. 2,8 ~ 12 mm motorized lens (103°~32,1°). ICR filter. OSD, ATW, AGC, BLC, WDR 120 dB, 3D-DNR, brightness, sharpness, mirror, motion detection and privacy mask. IP50. 3AXIS. 12V DC.
HYU-573		HDTV dome Starlight with Smart IR of 40 m, for outdoors. 2MP CMOS. HDTV output. 2,8~12 mm (103°~32,1°) motorized lens with autofocus. ICR. OSD, ATW/MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, mirror mode, brightness and sharpness adjustment, motion detection and privacy mask. IP67. 3AXIS. 12V DC.
HYU-548		HDTV dome Starlight with Smart IR of 40 m for outdoors. 2MP CMOS. HDTV output. 2,8 ~ 12 mm (103°~32,1°) motorized lens with autofocus. ICR. OSD, ATW/MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, mirror mode, brightness and sharpness adjustment, motion detection and privacy mask. IP67. 3AXIS. 12V DC.
HYU-508		HD-TVI TURBO HD StarLight bullet camera with Smart IR of 40 m for outdoors. 2MP CMOS. HDTV video output. 2,8 ~ 12 mm (103°~32,1°) motorized lens with autofocus. ICR filter. OSD, ATW/MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, mirror mode, brightness and sharpness adjustment, motion detection and privacy mask. IP67. 3AXIS bracket. 12V DC.
HYU-491		4 in 1 dome PRO series with Smart IR of 40 m for outdoors. 5MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,7 ~ 13,5 mm motorized lens (95,7°~29,1°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, brightness, sharpness, mirror. IP67. 3AXIS. 12V DC
HYU-489		4 in 1 bullet camera PRO series with Smart IR of 40 m for outdoors. 5MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,7 ~ 13,5 mm motorized lens (95,7°~29,1°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, brightness, sharpness, mirror. IP67. 3AXIS. DC12V.
HYU-490		4 in 1 vandal dome PRO series with Smart IR of 40 m, for outdoors. 5MP CMOS. 4 in 1 (HDCVI/HDTV/AHD/960H). 2,7 ~ 13,5 mm (95,7°~29,1°) motorized lens with autofocus. ICR. 0,01 lux. OSD, AWB, AGC, BLC, digital WDR, DNR, brightness, sharpness, mirror. IP67, IK10. 3AXIS. 12V DC.
HYU-572		HD-TVI dome PRO series with Smart IR of 40 m for outdoors. 5MP CMOS. HD-TVI video output. 2,7~13,5 mm motorized lens (95,7°~29,1°). ICR. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, image adjustment. IP67. 3AXIS. 12V DC. PoC.at compatible.
HYU-571		HD-TVI bullet camera PRO series with Smart IR of 40 m for outdoors. 5MP CMOS. HD-TVI video output. 2,7~13,5 mm motorized lens (95,7°~29,1°). ICR. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, image adjustment. IP67. 3AXIS bracket. 12V DC. PoC.at compatible.
HYU-291		HD-TVI fixed dome ULTRAPRO series with IR illumination of 40 m, for outdoors. 5MP CMOS. HD-TVI video output. 2,8~12 mm motorized lens (27,7°~86,8°). ICR filter. OSD, ATW, MWB, AGC, BLC, DNR, mirror. IP67. 12V DC.






ANALOG CAMERAS




Reference	Picture	Description
HYU-437		HD-TVI TURBO HD 4.0 bullet camera ULTRAPRO series with IR illumination of 40 m for outdoors. 8,3MP CMOS. Double video output HD-TVI/CVBS. 2,8 mm fixed lens (102,2°). ICR filter. OSD, ATW, MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, defog, mirror, privacy mask. IP67. 3AXIS bracket. 12V DC
HYU-438		HD-TVI TURBO HD 4.0 fixed dome ULTRAPRO series with IR illumination of 60 m, for outdoors. 8,3MP CMOS. Double video output HD-TVI/CVBS. 2,8 mm fixed lens (102,2°). ICR filter. OSD, ATW, MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, defog, mirror, privacy mask. IP67. 3AXIS. 12V DC.
HYU-435		HD-TVI TURBO HD 4.0 bullet camera ULTRAPRO series with IR illumination of 80 m, for outdoors. 8,3MP CMOS. HD-TVI/CVBS double video output. 2,8~12 mm motorized lens (108,1°~45,6°) with autofocus. ICR filter. OSD, ATW, MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, defog, mirror, privacy mask. IP67. 3AXIS. 12V DC.
HYU-436		HD-TVI TURBO HD 4.0 fixed dome ULTRAPRO series with IR illumination of 80 m for outdoors. 8,3MP CMOS. Double video output HD-TVI/CVBS. 2,8~12 mm motorized lens (108,1°~45,6°) with autofocus. ICR. OSD, ATW, MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, defog, mirror, privacy mask. IP67. 3AXIS. 12V DC.










DVR










Reference	Picture	Description
HYU-370		4 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 1 IP channel. H.265+/H265/H.264+/H264. 2 way audio. 4 channel playback at 1080P. Recording: 4M-N, 3MP (channel1, 15 fps, only TVI), 4MP (1 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA output at 1080P. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
HYU-527		4 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 1 IP channel. H.264+/H264. 2 way audio. Playback: 4 ch 720P. Recording 1080N, 720P, WD1, D1, VGA, CIF, QVGA, QCIF. HDMI and VGA simultaneous output at 1080P. Alarm: 4 in / 1 out. 1 HDD SATA. RJ45 Fast Ethernet. Onvif, P2P, DDNS. 2 USB. 12V DC.
HYU-373		4 channel 5 in 1 ZVR, HDCVI/HDTV/AHD/CVBS + 1 IP channel. H.265+/H265/H.264+/H264. 2 way audio. 4 channel playback at 1080P. Recording: 4M-N, 3MP (channel 1, 15 fps, only TVI), 4MP (1 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA output at 1080P. Alarm: 4 in / 1 out. 1 HDD SATA capacity. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
HYU-528		8 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channels 1080P. H.264+/H264. 2 way audio. 8 ch 720P. recording 1080N, 720P, WD1, D1, VGA, CIF, QVGA, QCIF. HDMI and VGA simultaneous output at 1080P. Alarm: 4 in / 1 out. 1 HDD SATA. RJ45 Fast Ethernet. Onvif, P2P, DDNS. 2 USB. 12V DC.








DVR		
Reference	Picture	Description
HYU-391		4 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 1 IP channels. H.265+/H265/H.264+/H264. 2 way audio. 4 channel playback 1080P. Recording 3MP (channels 1 to 4, 15 fps, only TVI), 4MP (2 IP inputs), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA at 1080P. 1 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485. DC48V. Compatible with PoC cameras.
HYU-371		8 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channel. H.265+/H265/H.264+/H264. 2 way audio. 8 channel playback at 1080P. Recording: 4M-N, 3MP (channel1 & 2, 15 fps, only TVI), 4MP (2 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA output at 1080P. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
HYU-236		16 channel 5 in 1 ZVR (HDCVI/HDTV/AHD/CVBS + 2 IP channel). H.264+/H.264. G.711u audio format. 2 way audio. 16 ch@720p. Recording: 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF, full 720p lite. HDMI and VGA output @ 1080p. 1HDD SATA. Onvif, P2P, DDNS, 2USB, 12VDC.
HYU-529		16 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channels 1080P. H.264+/H264. 2 way audio. 16 ch 720P. recording 1080N, 720P, WD1, D1, VGA, CIF, QVGA, QCIF. HDMI and VGA simultaneous output at 1080P. 1 HDD SATA. RJ45 Fast Ethernet. Onvif, P2P, DDNS. 2 USB. 12V DC.
HYU-562		4 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channel. H.265+/H265/H.264+/H264. Audio: 4 input / 1 output. 4 channel simultaneous playback. Recording: 6MP (IP), 5MP (TVI, AHD), 4MP, 1080P, 720P, WD1, 4CIF, VGA, CIF. BNC output at 4CIF. HDMI and VGA at 1080P. Alarm: 4 input / 1 output. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 48V DC. Compatible with PoC up to 5MP.
HYU-379		4 channel 5 in 1 TURBO HD 4.0 ZVR, 8MP (10FPS) / 5MP (20FPS) / 4MP (25FPS) / 3MP (18FPS) / 1080P (25FPS) HDCVI/HDTV/AHD/CVBS + 2 IP channels at 8MP. H.265+/H.265/H.264+/H264. Audio: 4 in / 1 out (2 way audio). Recording 8MP/5MP/4MP/3MP (TVI), 1080P/720P (CVI, AHD), WD1/4CIF/VGA/CIF (CVBS), full 4MP in all cameras. BNC a@ 4CIF output. HDMI (4K, 2K) and VGA (1080P) output. Alarm: 4 in / 1 out. 1 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 1 USB 2.0. 1 USB 3.0, 1 RS485. 12V DC.
HYU-392		8 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channel. H.265+/H265/H.264+/H264. 2 way audio. 8 channel playback at 1080P. Recording: 3MP (channel 1 and 2, 15 fps, only TVI), 4MP (2 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA output at 1080P. 2 HDD SATA capacity. Onvif, P2P, DDNS. 2 USB, 1 RS485. DC48V. Compatible with PoC cameras.
HYU-385		16 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channels. H.265+/H265/H.264+/H264. 2 way audio. 16 channel playback. Recording: 4MP (2 IP inputs), 4M-N, 3MP (channel 1 to 4, 15 fps, only TVI), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF (25 fps). HDMI and VGA output at 1080P. 1 HDD SATA capacity. Onvif, P2P, DDNS. 2 USB. 12V DC.
HYU-372		16 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channel. H.265+/H265/H.264+/H264. 2 way audio. 16 channel playback at 1080P. Recording: 4M-N, 3MP (channels 1 to 4, 15 fps, only TVI), 4MP (2 IP inputs), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI output at 4K and VGA at 1080P. 1 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.








DVR		
Reference	Picture	Description
HYU-375		16 channel ZVR 5 in 1 HDCVI/HDTVI/AHD/CVBS + 2 IP channels. H.265+/H265/H.264+/H264. 2 way audio. 16 channel playback at 1080P. Recording 4M-N, 3MP (channel 1 to 4, 15 fps, only TVI), 4MP (2 IP inputs), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI output at 4K and VGA output at 1080P. Alarm: 16 in / 1 out. 1 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
HYU-563		8 channel 5 in 1 ZVR HDCVI/HDTVI/AHD/CVBS + 4 IP channels. H.265+/H265/H.264+/H264. Audio: 4 in / 1 out. 8 channel simultaneous playback. Recording: 8MP (IP), 6MP (TVI, AHD), 4MP, 1080P, 720P, WD1, 4CIF, VGA, CIF. BNC output at 4CIF. HDMI and VGA output at 1080P. Alarm: 8 in / 4 out. 2 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 48V DC. PoC up to 5MP.
HYU-380		8 channel 5 in 1 TURBO HD 4.0 ZVR 8MP (10FPS) / 5MP (20FPS) / 4MP (25FPS) / 3MP (18FPS) / 1080P (25FPS) HDCVI/HDTVI/AHD/CVBS + 2 IP channel up to 8MP. H.265+/H.265/H.264+/H264. Audio: 8 in / 1 out (2 way audio). Recording: 8MP/5MP/4MP/3MP (TVI), 1080P/720P (CVI, AHD), WD1/4CIF/VGA/CIF (CVBS), full 4MP in all cameras. BNC output @ 4CIF. HDMI (4K, 2K) and VGA (1080P) output. Alarm: 8 in / 1 out. 2 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 1 USB 2.0. 1 USB 3.0, 1 RS485. 12V DC.
HYU-393		16 channel 5 in 1 ZVR HDCVI/HDTVI/AHD/CVBS + 2 IP channels. H.265+/H265/H.264+/H264. 2 way audio. 16 channel playback 1080P. Recording 3MP (channels 1 to 4, 15 fps, only TVI), 4MP (2 IP inputs), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI output at 4K and VGA at 1080P. 2 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485. DC48V. Compatible with PoC cameras.
HYU-231		16 channel 5 in 1 ZVR HDCVI/HDTVI/AHD/CVBS + 2 IP channels 4MP. H.264+/H264. Audio: 4 in / 1 out (2 way audio). Resolution per channel: 3 Mpx (12FPS) or 1080p, 1080PLite/720P (25FPS). BNC output at D1/4CIF. HDMI and VGA output at 1080P. Alarm: 16 in / 4 out. 2 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 1 USB 2.0, 1 USB 3.0, 1 RS485. 12V DC.

IPC		
Reference	Picture	Description
HYU-414		IP bullet camera with IR of 30m, for outdoors, 2 MP. H.265+, H.265, H.264+, H.264. 1/2,8" CMOS, 2MP. Digital resolution 1080P, 1,3MP, 720P, etc. Mechanical filter. 0,01 lux. 2,8 mm (103°) fixed lens. OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67. 3AXIS. 12V DC. PoE.
HYU-416		IP dome with IR illumination of 30m, for outdoors, 2 MP. H.265+, H.265, H.264+, H.264. 1/2,8" CMOS, 2MP. 1080P, 1,3MP, 720P, etc. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (95°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, ROI. IP67. 3AXIS. 12V DC. PoE.
HYU-415		IP vandal dome with IR illumination of 30m, for outdoors, 2 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2,8" CMOS, 2MP. Digital resolution 1080P, 1,3MP, 720P, etc. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (114°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67. 3AXIS. Reset button. 12V DC. PoE.

IPC		
Reference	Picture	Description
HYU-432		WiFi compact IP camera with IR illumination of 5 m for indoors. H.264. 1/2,8" CMOS, 2MP. Dual stream. Mechanical filter. 0,01 lux. 2,8 mm fixed lens. OSD, AGC, 3D-NR, digital WDR. Built in microphone and speaker. MicroSD/SDHC/SDXC. 5V DC.
HYU-408		IP bullet camera with IR illumination of 30m, for outdoors, 4 MP. Formato H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution: 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (100°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67. 3AXIS bracket. 12V DC. PoE.
HYU-410		IP dome with IR illumination of 30 meters, for outdoors, 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (100°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67. 3AXIS. 12V DC. PoE.
HYU-409		IP vandal dome with IR illumination of 30m, for outdoors, 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution: 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (100°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67, IK10. 3AXIS. Reset button. 12V DC. PoE.
HYU-298		IP WiFi compact camera with IR illumination of 5m, for indoors. H.264/MJPEG. 1/4" CMOS, 1MP. Dual stream. Mechanical filter. 0,01 lux. 2,8 mm fixed lens. OSD, AGC, 3D-NR, digital WDR. Microphone and speaker. Ranura MicroSD /SDHC / SDXC. 5V DC.
HYU-289		IP WiFi vandal dome with IR illumination of 30 m, for outdoors. H.264/MJPEG. 1/2,8" CMOS, 2MP. Dual stream. Mechanical filter. 0,028 lux. 2,8 mm fixed lens (106°). OSD, 3D-NR, BLC, digital WDR, ROI. IVS. MicroSD//SDHC/SDXC slot. IP66. 12V DC. PoE.
HYU-241		IP fixed vandal dome with IR illumination of 30 meters, for outdoors, 2MP. H.264/MJPEG. 1/3" CMOS, 2MP. 1080p/1.2MP/720p. Mechanical filter. 0.014 lux. 2.8~12 mm varifocal lens (113°~33.8°). OSD, 3D-NR, BLC, digital WDR, privacy mask, ROI, Intelligent functions (IVS). MicroSD/SDHC/SDXC. IP67, IK10. 3AXIS. 12V DC. PoE
HYU-496		WiFi IP compact camera with IR of 10m, for indoors, 4 MP. H.265+ /H.265 /H.264 /H.264+ /MJPEG. 1/3" CMOS, 4MP. 4MP, 3MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm (98°) fixed lens. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, ROI zones. Intelligent functions. Facial detection. 2 way audio. MicroSD/SDHC/SDXC. 12V DC. PoE.
HYU-417		IP bullet camera with IR illumination of 30 meters,for outdoors, 2 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2,8" CMOS, 2MP. 1080P digital resolution, 1,3MP, 720P, etc. Mechanical filter. 0,01 lux. 2,8~12 mm motorized lens (98°~34°) with autofocus. OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. SD slot. IP67. 3AXIS. Reset button. 12V DC. PoE.

IPC		
Reference	Picture	Description
HYU-419		IP vandal dome with IR of 30m, for outdoors, 2 MP. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,8" CMOS, 2MP. 1080P, 1,3MP, 720P, etc. Mechanical filter. 0,01 lux. 2,8~12 mm (98°~34°) motorized lens with autofocus. OSD, AGC, BLC, WDR digital, 3D-DNR, motion detection, privacy mask, fixed ROI. MicroSD/SDHC/SDXC. IP67, IK10. 3AXIS. Reset button. 12V DC. PoE.
HYU-494		IP dome with IR of 30m, for outdoors 6 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2,9" CMOS, 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm (97°) fixed lens. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. Intelligent functions. Facial detection. 2 way audio. MicroSD/SDHC/SDXC. IP67. 3AXIS. 12V DC. PoE.
HYU-495		WiFi IP compact camera Performance Line with IR illumination of 10m, for indoors, 6 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2,8" CMOS, 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm (80°) fixed lens. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. Intelligent functions. Facial detection. 2 way audio. MicroSD/SDHC/SDXC. 12V DC. PoE.
HYU-492		IP bullet camera Performance Line with IR of 30m, for outdoors 6 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2,9" CMOS, 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (97°). OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. intelligent function. Facial detection. 2 way audio. MicroSD/SDHC/SDXC slot. IP67. 3AXIS. 12V DC. PoE.
HYU-493		IP vandal dome Performance Line with IR of 30m, for outdoors 6 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2,9" CMOS, 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm (97°) fixed lens. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. Intelligent functions. Facial detection. 2 way audio. MicroSD/SDHC/SDXC. IP67, IK10. 3AXIS. 12V DC. PoE.
HYU-411		IP bullet camera with IR illumination of 30 m, for outdoors, 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8~12 mm motor lens (98°~28°) with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. SD slot. IP67. 3AXIS bracket. Reset button. 12V DC. PoE.
HYU-285		IP fixed dome with IR illumination of 40m, for outdoors. 8 MP. H.265/H.264/MJPEG. 1/2,5" CMOS, 8MP. Triple stream. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (102°). OSD, 3D-NR, BLC, real WDR 120dB, privacy mask, 1 ROI zone. IVS. MicroSD//SDHC/SDXC slot. IP67. 3AXIS. 12V DC. PoE.
HYU-356		WiFi IP dome with pan/tilt positioner and IR illumination up to 10m, for indoors, 2MP. H.264/H.264+/MJPEG. Digital resolution: 1080P (1920x1080), 1,3MP (1280x960), 720P (1280x720), etc. 2,8 mm fixed lens. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection and privacy mask, ROI zones. MicroSD/SDHC/SDXC slot. Reset button. 12V DC.
HYU-394		WiFi vandal IP dome with IR of 10 m, for outdoors, 4MP. H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Dual Stream. MEchanical filter. 0,01 lux. 2,8 mm fixed lens (106°). OSD, 3D-NR, BLC, real WDR 120dB, ROI. IVS. MicroSD//SDHC/SDXC. IP67, IK08. 12V DC. PoE.

IPC		
Reference	Picture	Description
HYU-498		WiFi IP dome Performance Line with IR of 10m, for outdoors, 6 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2,9" CMOS, 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm (80°) fixed lens. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, ROI fixed zone. Intelligent functions. Facial detection. MicroSD/SDHC/SDXC slot. IP67, IK08. 3AXIS. 12V DC. PoE.
HYU-396		Fixed IP vandal dome, IR illumination of 30m, for outdoors, 8 MP. H.265+ /H.265 /H.264+ /H.264 /MJPEG. 1/2,5" CMOS, 8MP. Triple stream. Mechanical filter. 0,014 lux. 2,8 ~12 mm motorized lens (115°~35°). OSD, 3D-NR, BLC, real WDR 120dB, motion detection, privacy mask, 1 ROI. IVS. Audio: 1 in / 1 out. Alarm: 1 in / 1 out. MicroSD/SDHC/SDXC. IP67, IK10, Lightning-proof 2KV. 12V DC. PoE.
HYU-397		Fixed IP vandal dome with IR illumination of 30 m., for outdoor, 8 MP. H.265+ /H.265 /H.264+ /H.264 / MJPEG. 1/2,5" CMOS, 8MP. Triple stream. Mechanical filter. 0,014 lux. 2,8 ~12 mm motorized lens (115°~35°). OSD, 3D-NR, BLC, real WDR 120dB, motion detection, privacy mask, 1 ROI. IVS. Audio: 1 in / 1 out. Alarm: 1 in / 1 out. MicroSD/SDHC/SDXC. IP67, IK10, Lightning-proof 2KV. 12V DC. PoE.
HYU-499		IP vandal bullet camera Performance Line with IR illumination of 50m, for outdoors 6 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2,9" CMOS of 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8~12 mm (88°~27°) motorized lens with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. Intelligent functions. Facial detection. 2 way audio. Alarm: 1 in / 1 out. MicroSD/SDHC/SDXC. IP67, IK10. 3AXIS. 12V DC. PoE+.
HYU-353		IP fisheye dome with IR illumination of 8 m, for indoors, 5 MP. H.264/H.264+/MJPEG. Digital resolution: 5MP (2560x1920), 3MP (2048x1536), 1,3MP (1280x960), etc. 1,05 mm fisheye lens, 180°. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection and privacy mask, fixed ROI zone. IVS. 14 dewarping modes. MicroSD/SDHC/SDXC slot. 3AXIS. Reset button. 12V DC. PoE.
HYU-519		IP smart camera for people counting. H.264. Dual stream. 1/3" CMOS. 640x960 resolution. 2 mm lens (100°) and 2,8 mm lens (82°). 3D-DNR, 1 ROI per stream, Brightness adjustments. Alarm: 1 in / 1 out. 12V DC. PoE.
HYU-544		IP fisheye vandal dome with IR of 15m, for outdoors. H.264/MJPEG. Digital resolution: 12MP (4000x3072), etc. 1,98 mm fisheye lens, 360°. OSD, AGC, BLC, digital WDR, 3D-DNR, 4 ROI. IVS. MicroSD/SDHC/SDXC. IP66, IK10. 12V DC. PoE.

NVR		
Reference	Picture	Description
HYU-523		4 channel IP NVR. H.265+/H.265/H.264+/H.264. 1 ch 4MP or 2 ch 1080P. 4MP display. Recording: 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. 40 Mbps. VGA and HDMI at 1080P. 1 HDD SATA. 2 USB. Compatible Onvif, P2P, DDNS. 12V DC. Desktop. 4x PoE+.
HYU-445		4 channel IP NVR. H.265/H.265+/H.264/H.264+/MPEG4. 4 channel 1080P or 1 channel 8MP. Display up to 8MP. Recording: 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, 4CIF, etc. Recording up to 40 Mbps. VGA @ 1080P and HDMI @ 4K output. Two way audio. 1 HDD SATA supported. Onvif, P2P, DDNS. 12V DC. 4 PoE+. Desktop
HYU-283		8 channel WiFi mini NVR. H.264/MPEG4. 8 channel synchronized playback. Display up ot 6MP. Recording 6MP, 5MP, 4MP, 3MP, 1080P, 720P, 4CIF, etc. recording up to 50 Mbps. HDMI video and audio output Full HD. 1 HDD SATA de 2,5" supported. WiFi 802.1b/g/n embedded router module. 2x2 MIMO antenna. 2,4GHz. Compatible with Onvif, P2P, DDNS. 12V DC.
HYU-524		8 channel IP NVR. H.265+/H.265/H.264+/H.264. 1 ch 4MP or 2 ch 1080P. 4MP display. Recording: 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. 60 Mbps. VGA and HDMI at 1080P. 1 HDD SATA. 2 USB. Compatible Onvif, P2P, DDNS. 12V DC. Desktop. 8x PoE+.
HYU-473		8 channel IP NVR with POS function. H.265/H.264+/H.264/MPEG4. 8 channel playback @ 1080P. Display up to 8MP. Recording 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, 4CIF, etc. Recording up to 80 Mbps. VGA @ 1080P and HDMI @ 4K output. 2 way audio. Alarm: 4 in / 1 out. 2 HDD SATA supported. RJ45 Gigabit. Up to 4 POS . 1 LPR channel supported. Compatible with Onvif, P2P, DDNS. 220V AC. 8 PoE+ ports.
HYU-520		16 CH IP NVR IP. H.265/H.264/MPEG4. 16 CH @ 1080P. Display up to 12MP. Recording: 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. Recording 160 Mbps. VGA @ 1080P and HDMI @ 4K. 2 way audio. Alarm: 4 in / 1 out. 2 HDD SATA. RJ45 Gigabit. POS function up to 4 POS. 1 LPR channel supported. Compatible with Onvif, P2P, DDNS. 220V AC. 16 PoE+ ports.
HYU-382		32 channel IP NVR, H.265+/H.265/H.264+/H.264/MPEG4. 16 channel playback at 1080P. Recording: 3MP (channels 1 to 4, 15 fps, only TVI), 4MP (2 IP inputs), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI output at 4K and VGA at 1080P. Alarm: 16 input / 1 output. 1 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.