

## KPT-39 Remote Keypad Series with Proximity Reader

## Easy and Secure Access at Your Fingertips



- A 15-button backlit keypad
- Integrate RFID key fobs or NFC tags

KPT-39 is a smart wireless remote keypad, offering users an easy-to-program solution to easily arm, disarm, and home arm their security system. For enhanced flexibility and convenience, KPT-39 series can integrate with RFID key fobs or NFC tags for secure quick access without entering pin codes manually.

To provide additional peace of mind and safety, KPT-39 series features dual key function that can activate panic, fire, or medical emergency alarm at the touch of a button. KPT-39 keypad can be wall-mounted at any location that is the most convenient and the most accessible in users' homes. KPT-39 is safeguarded by tamper protection.

KPT-39 leverages Climax's industry-leading RF technology to accelerate the speed of signal transmission and deliver reliable, extensive communication range. KPT-39 also features a power conservation function that consumes power only when in operation.

### Features

- Enables user to arm/disarm/home arm the security system by simply swiping RFID key fobs or NFC tags
- Integrates up to 100 RFID key fobs or NFC tags
- Dual key buttons to trigger panic, fire, or medical emergency alarms
- Stand-by mode for power saving function
- LED status indicators
- A 15-button backlit keypad for easy nighttime visibility
- Tamper protection against unauthorized removal
- Extensive RF communication range and faster signal transmission
- Regular supervision signals to check system integrity
- IP34 waterproof standard
- UL1023 compliant

### Specifications

#### KPT-39-F1

|                         |                               |
|-------------------------|-------------------------------|
| Frequency               | 868 MHz / 433 MHz             |
| Power Source            | 3V, CR123 Lithium battery x 1 |
| Battery Life            | 6 years*                      |
| Key Fob Reader Protocol | ISO 15693                     |
| Waterproof Rating       | IP34                          |
| Operating Temperature   | -10°C to 45°C (14°F to 113°F) |
| Operating Humidity      | Up to 85% non-condensing      |
| Dimensions              | 120 mm x 90 mm x 30 mm        |

## KPT-39 Remote Keypad Series with Proximity Reader

### KPT-39N-F1

|                       |                               |
|-----------------------|-------------------------------|
| Frequency             | 868 MHz / 433 MHz             |
| Power Source          | 3V, CR123 Lithium battery x 1 |
| Battery Life          | 6 years*                      |
| NFC Tag Dimensions    | 45 mm x 25 mm                 |
| NFC Protocol          | ISO 14443A                    |
| Waterproof Rating     | IP34                          |
| Operating Temperature | -10°C to 45°C (14°F to 113°F) |
| Operating Humidity    | Up to 85% non-condensing      |
| Dimensions            | 120 mm x 90 mm x 30 mm        |

\*Note: Actual battery life may vary due to device settings, operating environment and usage activity.

### Ordering Information

---

|                   |                                |
|-------------------|--------------------------------|
| <b>KPT-39-F1</b>  | Remote Keypad and RFID Key Fob |
| <b>KPT-39N-F1</b> | Remote Keypad and NFC Tag      |