

ZK-LPR Totem

Waterproof License Plate Recognition Totem

ZKTeco



Compatible with:



License: ABC123
Country: Portugal
Date: 13/11/2020

ZK-LPR Totem is a waterproof license plate recognition totem for ZK-LPR Car ID, a high-performance camera BL-852Q38A-LP with embedded LPR software. The LPR totem is designed to install an optional C3 access controller, as well as any third-party device, to enable access links between the camera and the security system.

The embedded LPR software in ZK-LPR Car ID executes a license plate recognition algorithm inside the camera for ease of use in access control, tolling and weighing scenarios. The License Plate Recognition engine can identify license plates from over 80 countries around the world.

ZK-LPR Car ID is the next step in ZKTeco's access control system technology for efficient and simple vehicle access management, delivering, faster & easier set-up and allowing customers to achieve high performance with lower installation, maintenance and off-site programming costs.

ZK-LPR Car ID with ZK-LPR Totem, is the ideal solution for outdoor vehicle access management, advanced license plate recognition and entrance control.

ZK-LPR Car ID is fully integrated into ZKBioSecurity Platform (parking module) for an integral and complete solution.



Allows integration with
server / cloud based
solutions



LPR software embedded
in the camera



Access lists for multiple
events configuration



Scalable solution with
primary / secondary cameras



OCR conversion directly in
the camera



Supports 3rd party
integration (Milestone
and Lenel)



Identifies plates from
more than 80 countries




Stainless steel waterproof
for outdoor installation




ZK-LPR Car ID allows real-time monitoring of alphanumeric license plates captured by the camera, issuing reports with plate recognition data. Optimized memory storage available.

The licences plate recognition history data can be stored for retrieval and review. Different filters can be enabled for this purpose, such as: Date, time, country of origin.



The system allows to create an unlimited number of event lists and assign different actions like, for example, opening/closing barriers sending a signal via HTTP or simple integrations with 3rd party companies like Milestone or Lenel. All linkages can be activated by limited time periods and lists can be exported or imported from other devices.

The system supports plate detection from different regions and countries. Country license plate detection is configurable as well as the performance of the camera according to the environment.



ZK-LPR Car ID is fully integrated into ZKBioSecurity "All in One" web based security platform (parking module) for an integral and complete solution.

* Optional

System elements



BL-852Q38A-LP

Network camera with
embedded LPR



IP65 Metal case

2 colors choice



**Access Control
Systems**

Optional





Parking barrier

Optional

Recognition features

- High Recognition Accuracy
- Recognition of 2-line vehicle plates
- Duplicated license plate filtering
- Access Control Linkage with ZKTeco Parking barriers
- LPR from vehicles in movement (up to 20 km/h) or stopped (Stop & Go).

Dimensions



Supported Countries

Spain	Netherlands	Austria	Brazil	Costa Rica	Vietnam	Abu Dhabi	Nigeria
Portugal	Estonia	Slovenia	Argentina	Dominican Republic	Indonesia	Dubai	Uganda
France	Bosnia and Herzegovina	Hungary	Mexico	Honduras	Philippines	Azerbaijan	Burkina Faso
Italy	Romania	Czech Republic	Ecuador	Nicaragua	Malaysia	Kuwait	Tanzania
United Kingdom	Belgium	Belarus	Venezuela	Bermuda	Singapore	Qatar	Kenya
Greece	Norway	Ukraine	Peru	Trinidad and Tobago	Israel	Saudi Arabia	Botswana
Ireland (ROI)	Denmark	Croatia	El Salvador	Barbados	Lebanon	Oman	Ghana
Germany	Sweden	Lithuania	Bolivia	Jamaica	Hong-Kong	South Africa	Cameroon
Andorra	Finland	Latvia	Uruguay	Russia	Macau	Morocco	EEUU
Poland	Gibraltar	Chile	Guatemala	Taiwan	India	Tunisia	Canada
Bulgaria	Switzerland	Colombia	Panama	Turkey	Bahrain	Angola	Australia
			Paraguay			Senegal	New Zealand

Specifications

Camera			
Model	BL-852Q38A-LP	Flash	512 Mb
Image Sensor	1/2.8" Sony STAVIS CMOS	IR LED No.	2 (Smart IR)
Effective Pixels	1920* 1080	IR Distance	50m
Min. Illumination	Color: 0.001Lux@F1.7 (AGC ON)	S/N Ratio	> 52dB
Lens			
Lens Type	Motorized	Aperture	F1.7 ~ F3.0
Mount Type	Board-in	FOV	38° ~ 107°
Focal Length	3.35mm ~ 10.05mm	Optical Zoom	3X
Video			
Compression	H.265+/H.265/H.264	WDR	TWDR
Resolution	1080P(1920*1080)/1.3MP(1280*960)/720P(1280*720) Q720P(640*360)/CIF(352*288)	Day/Night	Support
Bitrate Control	CBR/VBR	White Balance	Support
Bitrate	H.265+:1536Kbps-7Mbps H.265:1536Kbps-7Mbps H.264:1792Kbps-9Mbps	Defog	Support
Multi-Streaming	Main Stream:1080P@25fps	Noise Reduction	3D DNR
	Sub Stream: Q720P@25fps	Mirror/Flip	Support
	N/A	Corridor Mode	Support
Motion Detection	Support	HLC	Support
Digital Zoom	Support	BLC	N/A
Audio Compression	G7.11u	ROI	4 areas
Privacy Mask	5 areas	Anti-flicker	Support
Network			
Protocol	TCP/IP, UDP, HTTP, DHCP, RTSP, DDNS, NTP, PPPoE, UPnP, SMTP	Management Software(VMS)	AntarVis 2.0
Interoperability	ONVIF, SDK, API	Operation System	Windows
Max. Online Users	5	Mobile APP	AntarView Pro
Web Browser	IE/Firefox/Chrome/Safari	P2P Cloud Service	Support
Interface			
Ethernet	1 RJ-45 port (10/100Mbps)	Reset Button	Support
Audio I/O	1 in / 1 out	Micro-SD Slot	64GB MicroSD card included
Alarm I/O	2 in / 1 out	ANR	Support
RS485	Support	USB	N/A
General			
Power Supply	PoE (IEEE802.3af), DC 12V±10%	Working Humidity	10% ~ 90%
Power Consumption	< 3W	Working Temperature	-30°C ~ +60 °C
Ingress Protection	IP 67	Net Weight	0.50 kg
Dimensions	247(L)*85(W)*76(H)mm	Gross Weight	0.64 kg
Totem			
Environment	Indoor / Outdoor	Protection Level	IP65
Case Dimensions	265 x 225 x 700 mm	Case Material	Stainless steel