

## SpeedFace RFID

Access Control Terminal with Facial and Palm Recognition



Proactive Facial Recognition



New Height of Anti-Spoofing



Speedy Recognition



Wide Pose Angle Acceptance




Touchless for Better Hygiene



Wide Palm Pose Angle Acceptance



Compatible with  
**ZKBioSecurity**



Face



Card




Palm

## Features

- Visible Light Facial Recognition
- 3 in 1 Palm Recognition.
- Advanced Anti-spoofing algorithm against photo, video and 3D mask attack
- Multiple verification methods: Face / Card / Password / Palm
- Total Touchless Technology

## Recognition distance up to 2m and extra wide angle recognition


The facial recognition distance has been greatly extended up to 2 meters which significantly improves the maximum traffic rate and overall user experience. While most algorithms only support 15-degree pose angle facial recognition, ZKTeco supports 30-degree pose angle facial recognition.




## Specifications:

|                          |   |
|--------------------------|---|
| Display                  | 5-inch Touch Screen   |
| Face Capacity            | 6,000   |
| Palm Capacity            | 3,000   |
| Card Capacity            | 10,000  |
| Transactions             | 200,000   |
| Device Operation System  | Linux   |
| Standard Functions       | ID Card, ADMS, T9 Input, DST, Camera, 9 digit user ID, Access Levels, Groups, Holidays, Anti-passback, Record Query, Tamper Switch Alarm, Multiple Verification Modes |
| Hardware                 | 900MHZ Dual Core CPU  |
|                          | Memory 512MB RAM / 8G ROM   |
|                          | 2MP WDR Low Light Camera  |
|                          | Adjustable Light Brightness LED   |
| Communication            | TCP/IP, WIFI, Wiegand input/output, RS485   |
| Access Control Interface | 3rd Party Electric Lock, Door Sensor, Exit Button, Alarm output, Auxiliary Input  |
| Face Recognition Speed   | 1s  |
| Biometrics Algorithms    | ZKFace VX5.8 / ZKPalm VX12.0  |
| Power Supply             | 12V 3A  |
| Working Humidity         | 10%-90%   |
| Working Temperature      | -10 °C- 45 °C   |
| Dimensions               | (W*H*D) 91.93*202.93*21.5mm   |
| Supported Software       | ZKBioSecurity   |

## Configuration



## Dimensions (mm)



## Cable Management Box

